

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
1 December 2005 (01.12.2005)

PCT

(10) International Publication Number
WO 2005/113045 A1

(51) International Patent Classification⁷: **A61M 15/00**,
16/00

(21) International Application Number:
PCT/US2004/012061

(22) International Filing Date: 20 April 2004 (20.04.2004)

(25) Filing Language: English

(26) Publication Language: English

(71) Applicant and

(72) Inventor: **CRUTCHFIELD, Clifton, D.** [US/US]; 10851
N. Poinsettia, Tucson, AZ 85737 (US).

GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,
MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG,
PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM,
TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM,
ZW.

(84) Designated States (*unless otherwise indicated, for every
kind of regional protection available*): ARIPO (BW, GH,
GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),
Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), Euro-
pean (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR,
GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK,
TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW,
ML, MR, NE, SN, TD, TG).

Declaration under Rule 4.17:

— of inventorship (Rule 4.17(iv)) for US only

Published:


— with international search report

For two-letter codes and other abbreviations, refer to the "Guid-
ance Notes on Codes and Abbreviations" appearing at the begin-
ning of each regular issue of the PCT Gazette.

(74) Agent: **MILCZAREK-DESAI, Gavin, J.**; Quarles &
Brady Streich Lang, One South Church Avenue, Suite
1700, Tucson, AZ 85701 (US).

(81) Designated States (*unless otherwise indicated, for every
kind of national protection available*): AE, AG, AL, AM,
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,

(54) Title: RESPIRATOR FIT-TESTING APPARATUS AND METHOD



(57) Abstract: Improved respirator fit-test methods and apparatus featuring an automated, respirator wearer-controlled, air-leak measurement system. For fit testing of a respirator positioned on a test subject's face and connected to a controlled negative pressure testing apparatus, the test subject simply holds his breath and then activates a switch in electrical connection with said apparatus, which results in the automatic closure of the breathing port on the respirator and the initiation of a complete fit-testing protocol. The fit-testing apparatus includes a single, self-contained, automated unit that includes a vacuum source (30), an air-flow measuring device, and an air-pressure transducer (32) for connection to a respirator (10) being tested. By measuring the rate of air exhausted from the respirator in order to maintain a constant challenge pressure, an air leakage rate is determined.

WO 2005/113045 A1